

TECHNICAL SPECIFICATIONS 650HT SERIES

TOOL SIZE	6.50 inch (165 mm)
ASSEMBLY #	IA10043
AVAILABLE CONFIGURATIONS	PowerPulse® ActiPulse®
ActiPulse® DROP BALL SIZES	1.250 inch (32 mm) 1.375 inch (35 mm) 1.500 inch (38 mm)
LENGTH	Standard: 208 inch (5.28 m) Flex Option: 220 inch (5.59 m)
OPERATING FLOW RANGE <i>HIGH FLOW OPTION</i>	350 to 700 GPM (1.30 to 2.65 m ³ /min) <i>Up to 850 GPM (3.22 m³/min)</i>
FREQUENCY RANGE	6 to 11 Hz
PRESSURE DROP	500-725 psi (3500-5000 kPa)
MAX TEMPERATURE *	Standard: 285°F (140°C) Hi-temp: 375°F (190°C)
STANDARD END CONNECTIONS	DS 50
TORSIONAL STRENGTH *	58,000 Ft-lbs (78,000 N-m)
TENSILE STRENGTH *	750,000 lbs (336,000 daN)
RECOMMENDED MAXIMUM PULL *	562,000 lbs (250,000 daN)

SAFETY JOINT AVAILABLE UPON REQUEST

* For operating parameters outside listed specifications, consult with Impulse Representative



IMPULSE DOWNHOLE TOOLS

No part of this publication may be reproduced, distributed, or transmitted in any form or by any means without the written consent of Impulse Downhole Tools. All end thread connections may be either certified or industry standard compatible. US and Canadian Patents Granted and Patents Pending Worldwide

<https://www.impulsedownhole.com/patents>