

TECHNICAL SPECIFICATIONS 525HT SERIES

TOOL SIZE	5.25 inch (133 mm)
ASSEMBLY #	IA10024
AVAILABLE CONFIGURATIONS	PowerPulse® ActiPulse®
ActiPulse® DROP BALL SIZES	1.125 inch (29 mm) 1.250 inch (32 mm) 1.375 inch (35 mm)
LENGTH	Standard: 200 inch (5.08 m) Flex Option: 266 inch (6.77 m)
OPERATING FLOW RANGE	211 to 400 GPM (0.80 to 1.5 m³/min)
FREQUENCY RANGE	8 to 16 Hz
PRESSURE DROP	500-725 psi (3500 to 5000 kPa)
MAX TEMPERATURE *	Standard: 285°F (140°C) Hi-temp: 375°F (190°C)
STANDARD END CONNECTIONS	DS 40
TORSIONAL STRENGTH *	35,000 Ft-lbs (47,400 N-m)
TENSILE STRENGTH *	584,000 lbs (260,000 daN)
RECOMMENDED MAXIMUM PULL *	439,000 lbs (195,000 daN)

SAFETY JOINTS AVAILABLE UPON REQUEST

* For operating parameters outside listed specifications, consult with Impulse Representative



IMPULSE DOWNHOLE®