

TECHNICAL SPECIFICATIONS **ULTRA** 713HT SERIES

TOOL SIZE	7.13 inch (181 mm)
ASSEMBLY #	IA10267
AVAILABLE	PowerPulse®
CONFIGURATIONS	ActiPulse [®]
ActiPulse® DROP BALL SIZES	1.250 inch (32 mm) 1.375 inch (35 mm) 1.500 inch (38 mm)
LENGTH	234 inch (5.94 m)
OPERATING FLOW RANGE HIGH FLOW OPTION	550 to 800 GPM (2.08 to 2.84 m³/min) Up to 1,000 GPM (3.79 m³/min)
FREQUENCY RANGE	7 to 10 Hz
PRESSURE DROP	500-725 psi (3500 to 5000 kPa)
MAX TEMPERATURE *	Standard: 285°F (140°C) Hi-temp: 375°F (190°C)
STANDARD END CONNECTIONS	DS 55
TORSIONAL STRENGTH *	92,000 Ft-lbs (124,735 N-m)
TENSILE STRENGTH *	982,468 lbs (437,023 daN)
RECOMMENDED MAXIMUM PULL*	736,800 lbs (327,745 daN)

SAFETY JOINT AVAILABLE UPON REQUEST



^{*} For operating parameters outside listed specifications, consult with Impulse Representative